

## ITY3-EM060LB-K

# ITYS EM+ CPSS 1/1 230V ON-LINE VFI - EXTERNAL BATTERY



The EMergency CPSS range (Emergency Central Power Supply System) has been designed to answer your needs in terms of power supply for your safety system. All our Emergency products are compliant with standard EN 50171.

### Strong points

- EN 50171 compliant
- Robust with high availability
- Flexible autonomy
- Easy and error-free installation

### General characteristics

- Embedded dry-contact interface.
- Input mains switch breaker.
- Connection for battery extension modules.
- Power off the UPS remotely.
- Internal temperature sensor.

### Compliance with standards

- EN 50171

### Access to resources (ex: manuals)

### Classification

|            |          |
|------------|----------|
| UNSPSC     | 39121011 |
| ETIM Class | EC000382 |
| IGCC       | 4149     |

### Commerce

|                         |                                                                                                     |
|-------------------------|-----------------------------------------------------------------------------------------------------|
| Description (240 char.) | ITYS EM+ CPSS 6 kVA / 6 kW / (5 kW COMPLIANCE EN50171:2001) 1/1 230V ON-LINE VFI - EXTERNAL BATTERY |
| Effective date          | 2021-07-15                                                                                          |
| Country of origin       | CN                                                                                                  |
| Weight [kg]             | 13.5                                                                                                |

### Logistics

|                |               |
|----------------|---------------|
| GTIN/EAN       | 8027122765602 |
| Customs number | 8504408590    |

### Norms

|                         |     |
|-------------------------|-----|
| Conformity to standards | IEC |
|-------------------------|-----|

### Technical Characteristics

|                 |       |
|-----------------|-------|
| Depth [mm]      | 416   |
| Height          | 354   |
| In/out          | 1/1   |
| Output voltage  | 230   |
| Rated frequency | 50/50 |
| Width           | 225   |
| Sn [kVA]        | 6     |
| Pn [kW]         | 5     |
| Input voltage   | 230   |
| Rate (min)      | 6     |
| Rate (max)      | 6     |