

NRT2-U2200C
NETYS RT-M 2,2KVA BAT+COATING

NETYS RT M is an easy to use, high-performance single-phase rack-tower UPS certified for marine applications.


Strong points

- High availability in marine environments
- Easy to use
- Meets practical needs

General characteristics

- Built-in backfeed protection.
- Protection against atmospheric phenomena (NTP) for telephone/ADSL modems.
- RJ11 connection for Emergency Power Off (EPO).
- Connection for battery extension modules.

Compliance with standards

- IEC/EN 62040-1, IEC/EN 62040-2, IEC/EN 62040-3
- AS 62040.1.1, AS 62040.1.2, AS 62040.2
- CE
- RCM (E2376)

Access to resources (ex: manuals)
Classification

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

Commerce

Description (240 char.)	NeTYS RT-M 2200VA/1800W 230V 50/60Hz ON-LINE DOUBLE CONVERSION (VFI) 1xEPO,1xUSB,1xRS232 BATTERY INCLUDED,PCB TROPICALISATION
Effective date	2017-01-01
Country of origin	CN
Length of the product unit [mm]	0.089
Width of the product unit [mm]	0.44
Depth of the product unit [mm]	0.43
Weight [kg]	19

Logistics

GTIN/EAN	8027122601177
Customs number	8504409590
Weight of the packing unit [kg]	19
Length of the packing unit [mm]	0.43
Width of the packing unit [mm]	0.44
Depth of the packing unit [mm]	0.089

Norms

Conformity to standards	IEC
-------------------------	-----

Technical Characteristics

Depth [mm]	430
Height	89
In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	440
Sn [kVA]	2.2
Pn [kW]	1.8
Conf	C1
Input voltage	230
Rate (min)	2.2
Rate (max)	2.2
Life Time	03-05
Typical Backup Time [min]	7
Configuration	UPS Single Unit(s) with Bypass